

GenFlex™ TYPE SC ENTERTAINMENT CABLE

600V
Durable CPE Jacket
-50°C to + 105°C
Indoor or Outdoor Use



AWG	Stranding/ Diameter	Nominal Insulation Thickness		Nominal O.D.		Standard Package	Shipping Weight	Ampacity
	in.	in.	mm	in.	mm		lbs./1000 ft.	A
6	7x37/.010	0.110	2.79	0.420	10.67	500	149	105
4	7x60/.010	0.110	2.79	0.480	12.19	500	212	140
2	7x95/.010	0.110	2.79	0.530	13.21	500	299	190
1	19x44/.010	0.110	2.79	0.580	14.73	500	369	220
1/0	19x56/.010	0.110	2.79	0.630	16.00	500	458	260
2/0	19x70/.010	0.110	2.79	0.680	17.27	500	558	300
3/0	19x88/.010	0.110	2.79	0.730	18.54	500	676	350
4/0	19x111/.010	0.110	2.79	0.790	20.07	500	826	405



Designed for use in temporary power supply applications such as TV, indoor and outdoor theaters, sound or lighting systems, and stages

Highly Flexible

Annealed 30 gauge bare copper conductor, insulated with a high grade RoHS compliant CPE - separator may be utilized to enhance stripability

Durable Jacket

Resists oil, solvents, ozone, crushing and abrasion

Operating Temperatures

-50°C to + 105°C
 (-58°F to +221°F)

Rated to 600 Volts

UL Subject 1680, CSA PPC 22.2 - 96

National Electrical Code
 article 520, 525, 530

ISO CERTIFICATIONS

ISO 9001: 2008 CERTIFIED
 ISO 14001: 2004 CERTIFIED

Indent Printing

Customizable print,
 available on all sizes

Custom Surface Print and Lengths

Options available

Sizes

#8 - 250MCM

Stock Color

Black



GENERGY HEADQUARTERS
 P.O. BOX 10731
 LANCASTER, PA 17605

WAREHOUSES
 Edmonton, AB
 Houston, TX
 Jacksonville, FL
 Lancaster, PA
 Valencia, CA

GENERGYPOWERUSA.COM
 Phone 717-584-0375
 Fax 717-704-8445
 Toll-Free 800-308-1330

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.



LISTED
E123385

MADE IN USA