



# GILLETTE GENERATORS

LIQUID COOLED NAT. GAS ENGINE GENERATOR SET

60 HZ MODEL

**SP-6500**

Model	STANDBY 130°C RISE		
	HZ	LPG	N.G.
<b>SP-6500-60 HERTZ</b>	60	420	650



All generator sets are USA prototype built and thoroughly tested. Production models are USA factory built and 100% load tested.



**UL2200, UL1446, UL508, UL142, UL498**



**NFPA 110, 99, 70, 37**

All generator sets meet NFPA-110 Level 1, when equipped with the necessary accessories and installed per NFPA standards.



**NEC 700, 701, 702, 708**



**NEMA ICS10, MG1, ICS6, AB1**



**ANSI C62.41, 27, 59, 32, 480, 40Q, 81U, 360-05**




**ASCE 7-05 & 7-10**

All generator sets meet 180 MPH rating.




**EPA 40CFR Part 60, 1048, 1054, 1065, 1068**



“OPEN” GEN-SET

There is no enclosure, so gen-set must be placed within a weather protected area, un-inhabited by humans or animals, with proper ventilation. Silencer not supplied, as installation requirements are not known. However, this item is available as optional equipment.



“LEVEL 2” HOUSED GEN-SET

Full aluminum weather protection and superior sound attenuation for specific low noise applications. Critical grade muffler is standard.

## GENERATOR RATINGS

					LIQUID PROPANE GAS FUEL		NATURAL GAS FUEL	
GENERATOR MODEL	VOLTAGE		PH	HZ	130°C RISE STANDBY RATING		130°C RISE STANDBY RATING	
	L-N	L-L			KW/KVA	AMP	KW/KVA	AMP
<b>SP-6500-3-2</b>	120	208	3	60	420/525	1458	650/812	2258
<b>SP-6500-3-3</b>	120	240	3	60	420/525	1264	650/812	1957
<b>SP-6500-3-4</b>	277	480	3	60	420/525	632	650/812	978
<b>SP-6500-3-5</b>	127	220	3	60	420/525	1379	650/812	2135
<b>SP-6500-3-16</b>	346	600	3	60	420/525	505	650/812	783

RATINGS: All three phase gen-sets are 12 lead windings, rated at .8 power factor. 130°C “STANDBY RATINGS” are strictly for gen-sets that are used for back-up emergency power to a failed normal utility power source. This standby rating allows varying loads, with no overload capability, for the entire duration of utility power outage. All gen-set power ratings are based on temperature rise measured by resistance method as defined by MIL-STD 705C and IEEE STD 115, METHOD 6.4.4. All generators have class H (180°C) insulation system on both rotor and stator windings. All factory tests and KW/KVA charts shown above are based on 130°C (standby) R/R winding temperature, within a maximum 40°C ambient condition. Generators operated at standby power ratings must not exceed the temperature rise limitation for class H insulation system, as specified in NEMA MG1-22.40. Specifications & ratings are subject to change without prior notice.

# APPLICATION AND ENGINEERING DATA FOR MODEL SP-6500-60 HZ

## GENERATOR SPECIFICATIONS

Manufacturer.....Stamford Electric Generators  
Model & Type..... HCI634G.311, 4 Pole, 12 Lead, Three Phase  
..... HCI534F.311, 4 Pole, 12 Lead, 480V, Three Phase  
..... HCI534F.07, 4 Pole, 6 Lead, 600V, Three Phase  
Exciter.....Brushless, shunt excited  
Voltage Regulator.....Solid State, HZ/Volts  
Voltage Regulation.....1/2%, No load to full load  
Frequency.....Field convertible, 60 HZ to 50 HZ  
Frequency Regulation.....1/2% (1/2 cycle, no load to full load)  
Unbalanced Load Capability.....100% of standby amps  
Total Stator and Load Insulation.....Class H, 180°C  
Temperature Rise.....130°C R/R, standby rating @ 40°C amb.  
3 Ø Motor Starting @ 30% Voltage Dip (208-240V)...1500 kVA  
3 Ø Motor Starting @ 30% Voltage Dip (480V-600V) 2140 kVA  
Bearing.....1, Pre-lubed and sealed  
Coupling.....Direct flexible disc  
Total Harmonic Distortion.....Max 3 1/2% (MIL-STD705B)  
Telephone Interference Factor.....Max 50 (NEMA MG1-22)  
Deviation Factor.....Max 5% (MIL-STD 405B)  
Ltd. Warranty Period.....24 Months from date of start-up or  
.....1000 hours use, first to occur.

## GENERATOR FEATURES

- World Renown Stamford Electric Generator having UL-1446 certification on full amortisseur windings.
- Full generator protection with **Deep Sea 7420** controller, having UL-508 certification.
- Automatic voltage regulator with over-excitation, under-frequency compensation, under-speed protection, and EMI filtering. Entire solid-state board is encapsulated for moisture protection.
- Generator power ratings are based on temperature rise, measured by resistance method, as defined in MIL-STD 705C and IEEE STD 115, Method 6.4.4.
- Power ratings will not exceed temperature rise limitation for class H insulation as per NEMA MG1-22.40.
- Insulation resistance to ground, exceeds 1.5 meg-ohm.
- Stator receives 2000 V. hi-potential test on main windings, and rotor windings receive a 1500 V. hi-potential test, as per MIL-STD 705B.
- Complete engine-generator torsional acceptance, confirmed during initial prototype testing.
- Full load testing on all engine-generator sets, before shipping.
- Self ventilating and drip-proof & revolving field design

## ENGINE SPECIFICATIONS AND APPLICATIONS DATA

### ENGINE

Manufacturer.....Power Solutions Inc. (PSI)  
Model and Type.....Heavy Duty, 31.8LTCAC HO, 4 cycle  
Aspiration.....Turbocharged & Charge Air Cooled  
Cylinder Arrangement.....12 Cylinders, Vee  
Displacement Cu. In. (Liters).....1941 (31.8)  
Bore & Stroke In. (Cm.).....5.91 x 5.91 (150 x 150)  
Compression Ratio.....10.5:1  
Main Bearings & Style.....14, Precision Half-Shell  
Cylinder Head.....Cast Iron  
Pistons.....Cast Aluminum  
Crankshaft.....Forged Steel  
Exhaust Valve.....Inconel, A193  
Governor.....Electronic  
Frequency Reg. (no load-full load).....Isochronous  
Frequency Reg. (steady state).....± 1/4%  
Air Cleaner.....Dry, Replaceable Cartridge  
Engine Speed.....1800  
Piston Speed, ft/min (m./min).....1772 (450)  
Max Power, bhp (kwm) Standby/LPG.....637 (475)  
Max Power, bhp (kwm) Standby/NG.....966 (720)  
Ltd. Warranty Period.....12 Months or 2000 hrs., first to occur

### FUEL SYSTEM

Type.....LPG or NAT. GAS, Vapor Withdrawal  
Fuel Pressure (kpa), in. H<sub>2</sub>O\*.....(1.74-2.74), 7"-11"  
Secondary Fuel Regulator.....NG or LPG Vapor System  
Auto Fuel Lock-Off Solenoid.....Standard on all sets  
Fuel Supply Inlet Line.....(2) 3" NPTF

### FUEL CONSUMPTION

LP GAS: FT <sup>3</sup> /HR (M <sup>3</sup> /HR)	STANDBY
100% LOAD	2490 (70.5)
75% LOAD	1844 (52.2)
50% LOAD	1309 (37.1)
LPG = 2500 BTU X FT <sup>3</sup> /HR = Total BTU/HR LPG Conversion: 8.50 FT <sup>3</sup> = 1 LB. : 36.4 FT <sup>3</sup> = 1 GAL.	

NAT. GAS: FT <sup>3</sup> /HR (M <sup>3</sup> /HR)	STANDBY
100% LOAD	6820 (193.1)
75% LOAD	5236 (148.3)
50% LOAD	3828 (108.4)
25% LOAD	2420 (68.5)
NG = 1000 BTU X FT <sup>3</sup> /HR = Total BTU/HR	

### OIL SYSTEM

Type.....Full Pressure  
Oil Pan Capacity qt. (L).....95 (90)  
Oil Pan Cap. W/ filter qt. (L).....119 (113)  
Oil Filter.....6, Replaceable Spin-On

### ELECTRICAL SYSTEM

Ignition System.....Electronic  
Eng. Alternator/Starter: 24 VDC, negative ground, 55 amp/hr.

Recommended battery to -18°C (0° F): ....(2) 12 VDC, BCI# 31,  
Max. Dimensions: 14"lg x 6 3/4" wi x 10" hi, with standard  
round posts. Min output 1400 CCA. Battery tray (max. dim. at  
15"lg x 7"wi). This model has (2) battery trays, (2) hold down  
straps, (2) sets of battery cables, and (1) battery charger.  
Installation of (2) 12VDC starting batteries connected in series  
for 24VDC output is required, with possible higher AMP/HR  
rating, as described above, if the normal environment  
temperature averages -13° F (-25°C) or cooler.

# APPLICATION AND ENGINEERING DATA FOR MODEL SP-6500-60 HZ

## COOLING SYSTEM

Type of System ..... Pressurized, closed recovery  
Coolant Pump ..... Pre-lubricated, self-sealing  
Cooling Fan Type (no. of blades) ..... Pusher (10)  
Fan Diameter inches (mm) ..... 68" (1727)  
Ambient Capacity of Radiator °F (°C) ..... 125 (51.6)  
Engine Jacket Coolant Capacity Gal (L) ..... 23.3 (88.1)  
Radiator Coolant Capacity Gal. (L) ..... 39 (148)  
Maximum Restriction of Cooling Air Intake  
and discharge side of radiator in. H<sub>2</sub>O (kpa) ..... 0.5 (.125)  
Water Pump Flow gpm (L/min) ..... 436 (1650)  
Heat Reject Coolant: Btu/min (kw) ..... 34,074 (599)  
Low Radiator Coolant Level Shutdown ..... Standard  
Note: Coolant temp. shut-down switch setting at 230°F (110°C) with 50/50  
(water/antifreeze) mix.

## AIR REQUIREMENTS

Combustion Air, cfm (m<sup>3</sup>/min) ..... 1396 (40)  
Radiator Air Flow cfm (m<sup>3</sup>/min) ..... 65,100 (1843)  
Heat Rejected to Ambient:  
Engine: kw (btu/min) ..... 146 (8310)  
Alternator: kw (btu/min) ..... 65 (3696)

## EXHAUST SYSTEM

Exhaust Outlet Size ..... (2) 6"  
Max. Back Pressure, in. hg (KPA) ..... 3.0 (10.2)  
Exhaust Flow, at rated kw: cfm (m<sup>3</sup>/min) ..... 4079 (115)  
Exhaust Temp., at rated kw: °F (°C) ..... 1183 (639)  
Engines are EPA certified for Natural Gas.

## SOUND LEVELS MEASURED IN dB(A)

	Open Set	Level 2 Encl.
Level 2, Critical Silencer .....	97	86
Level 3, Hospital Silencer .....	92	80

Note: Open sets (no enclosure) has (2) optional silencer system choices due to unknown job-site applications. Level 2 enclosure has installed critical silencer with upgrade to hospital silencer. Sound tests are averaged from several test points and taken at 23 ft. (7 m) from source of noise at normal operation.

## DERATE GENERATOR FOR ALTITUDE

3% per 1000 ft.(305m) above 3000 ft. (914m) from sea level

## DERATE GENERATOR FOR TEMPERATURE

2% per 10°F(5.6°C) above 104°F (40°C)

## DIMENSIONS AND WEIGHTS

	Open Set	Level 2 Enclosure
Length in (cm).....	186 (472)	246 (625)
Width in (cm).....	92 (234)	92 (234)
Height in (cm).....	98 (249)	116 (295)
3 Ø Net Weight lbs (kg).....	15950 (7235)	16440 (7457)
3 Ø Ship Weight lbs (kg) .....	16340 (7412)	18840 (8546)

# DEEP SEA 7420 DIGITAL MICROPROCESSOR CONTROLLER



### DEEP SEA 7420

The 7420 controller is an auto start mains (utility) failure module for single gen-set applications. This controller includes a backlit LCD display which continuously displays the status of the engine and generator at all times.

The 7420 controller will also monitor speed, frequency, voltage, current, oil pressure, coolant temp., and fuel levels. These modules have been designed to display warning and shut down status. It also includes: (11) configurable inputs • (8) configurable outputs • voltage monitoring • mains (utility) failure detection • (250) event logs • configurable timers • automatic shutdown or warning during fault detection • remote start (on load) • engine preheat • advanced metering capability • hour meter • text LCD displays • protected solid state outputs • test buttons for: stop/reset • manual mode • auto mode • lamp test • start button • power monitoring (kWh, kVAr, kVAh, kVArh)

This controller includes expansion features including RS232, RS484 (using MODBUS-RTU/TCP), direct USB connection with PC, expansion optioned using DSENet for remote annunciation and remote relay interfacing for a distance of up to 3300FT. The controller software is freely downloadable from the internet and allows monitoring with direct USB cable, LAN, or by internet via the built in web interface.



Further expansion is available by adding the optional "WebNet" gateway interface module. This device will allow comprehensive monitoring of the generator via the cloud including identification, location, and status. Some advantages of this module include: reduced site visits and maintenance costs • remote fuel management • fault analysis • asset tracking • automatic system alerts • maximized system up-time.

# STANDARD FEATURES FOR MODEL SP-6500-60 HZ

## STANDARD FEATURES

### CONTROL PANEL:

Deep Sea 7420 digital microprocessor with logic allows programming in the field. Controller has:

- STOP-MANUAL-AUTO modes and automatic engine shutdowns, signaled by full text LCD indicators:
- Low oil pressure
- High engine temp
- Low Radiator Level
- Three auxiliary alarms
- Battery fail alarm
- Engine fail to start
- Engine over speed
- Engine under speed
- Over & under voltage

Also included is tamper-proof engine hour meter

### ENGINE:

Full flow oil filter • Air filter • Oil pump • Solenoid type starter motor • Hi-temp radiator • Jacket water pump • Thermostat • Pusher fan and guard • Exhaust manifold • 24 VDC battery charging alternator • Flexible exhaust connector • "Isochronous" duty, electronic governor • Secondary dry fuel regulator • Dry fuel lock-off solenoid • Vibration isolators • Closed coolant recovery system with 50/50 water to anti-freeze mixture • flexible oil & radiator drain hose.

### AC GENERATOR SYSTEM:

AC generator • Shunt excited • Brushless design • Circuit Breaker installed and wired to gen-set • Direct connection to engine with flex disc • Class H, 180°C insulation • Self ventilated • Drip proof construction • UL Certified

### VOLTAGE REGULATOR:

½% Voltage regulation • EMI filter • Under-speed protection • Over-excitation protection • total encapsulation

### DC ELECTRICAL SYSTEM:

Battery tray • Battery cables • Battery hold down straps • 2-stage battery float charger with maintaining & recharging automatic charge stages

### WEATHER/SOUND PROOF ALUMINUM HOUSING CORROSION RESISTANT PROTECTION CONSISTING OF:

- 9 Heated and Agitated Wash Stages
- Zinc Phosphate Etching-coating Stage
- Final Baked On Enamel Powder Coat
- 18/8 Stainless Steel Hardware

Design & specifications subject to change without prior notice. Dimensions shown are approximate. Contact Gillette for certified drawings. DO NOT USE DIMENSIONS FOR INSTALLATION PURPOSES.

