



9. ELECTRICAL CONNECTOR FOR LIGHTS IS STANDARD SIX PRONG. MATING VEHICLE CONNECTOR PROVIDED.

8. TRAILER HAS ELECTRIC BRAKES WHICH ACTUATE BRAKES ON BOTH AXLES. SEE TRAILER MANUAL FOR DETAILS.

7. REVIEW TRAILER MANUAL, TOW VEHICLE MANUAL AND LOAD BANK MANUAL PRIOR TO TOWING.

6. TRAILER AXLE POSITION SET BY FACTORY BASED ON MINIMAL LOAD (WEIGHT) OR EQUIPMENT ADDED TO REEL AND OR TO FRONT OPEN DECK AREA OF TRAILER. HITCH WEIGHT MUST BE BETWEEN 8-15% FOR PROPER TOWING. DO NOT BLOCK LOAD BANK INTAKE AREA IF EQUIPMENT ADDED TO FRONT DECK AREA.

5. TRAILER PRIMED & FINISH PAINTED BLACK IN COLOR.

4. TRAILER RATING: 4400 LBS [1996 kg] GVWR

3. DIMENSIONS ARE IN INCHES [mm].

2. ALL DIMENSIONS ARE APPROX.

1. WEIGHT: 3400 LBS [1542 kg], WITHOUT CABLES

NOTES:

AVTRON
POWER SOLUTIONS

TRAILER MOUNT LOAD BANK
GENERAL REFERENCE OUTLINE DRAWING

Model 5500

Rev -