



Universal R1250H Trailer-Mounted Load Bank Package



Our Universal R1250H Trailer-Mounted Resistive Load Bank Package offers a ULB 1250kW load bank, our heavy-duty trailer, our two cable reels with reel covers, and two cable sets.



ULB R1250H LOAD BANK

Load Capacity: 1250kW at 480VAC 3PH 60Hz, 800kW at 240VAC 3PH 60Hz, & 600kW at 208VAC 3PH 60Hz.*

Full Load Amps at 800kW: 1923 Amps at 240 VAC.

Full Load Amps at 1250kW: 1502 Amps at 480 VAC.

Duty Cycle: Rated for continuous operation.

Load Step Resolution: 5kW at 240/480V.

Controls: Local digital color touchscreen controller.

Instrumentation: Digital metering (V, A, kW) and data logging.

Control Power: Control power via internal dual voltage transformer or from external 120V 1Ph source.

Cooling Power: Blower power from connected load or external 480/240 3Ph source.

Cooling System: Integral forced-air cooling system with horizontal airflow. Removable sliding covers with lock pins on air intakes and exhausts.

Load Elements: ULB high-capacity chromium alloy load elements. Elements are fully supported with stainless steel rods and high temperature refractory ceramics for quick heat discharge.

Safety Features: Over-temperature, over/under voltage, and cooling-air loss protection. Also includes a hard-wired emergency stop switch.

Load Connections: Quick disconnect cam-type male connectors (9 per Phase, 5 Ground).

Daisy Chained: Multiple load banks can be paralleled for higher load capacity, and operated from a single controller.

Enclosure: Heavy gauge steel outdoor enclosure with powder coat finish. Designed to NEMA 3R standards for outdoor operation. Hinged access doors. Forklift pockets for easy mobility.

* Capacity rated up to 2,000 feet elevation from sea level. Please inquire for higher elevations.



Coffman Electrical Equipment Company, 3300 Jefferson Ave. SE, Grand Rapids, MI 49548
Phone: 616-452-8708, 1-800-852-7699 - Email: customerservice@steadypower.com

STEADYPOWER SP2-9900-190×99 TRAILER

Trailer: Galvanized steel.

GVWR: 9900 lbs.

Bed Size: 190" L x 99" W.

Axles: Tandem. Each axle rated 6,000 lbs.

Tires: Four Wheel-Mounted Goodyears.

DOT Approved: Lighting and 7-pin Electrical Connections.

Brakes: Electric.

Hitch: Choice of Ball or Pintle Hitch.

Jacks: One 7000-lbs Front Tongue Jack and Two Rear Swing-up Stabilizer Jacks.

Safety: Chains and Hooks.

D-Rings: Four Heavy-Duty.

Spare Tire: Mounted Goodyear.



STEADYPOWER SP-HRXCVCV-115VAC-1250 CABLE REEL

Linear Feet Capacity: Each reel holds up to 1250 ft of 4/0 cable.

50ft Cables Capacity: Each reel holds up to twenty-five 50ft 4/0 cables with cams.

Unwind/Rewind: 115VAC Electric motor with variable speed control and rocker switch.

Brake: Bearing mounted strap brake.

Hand Control: Enhanced push button switch.

Bonus Foot Control: Foot switch with 15ft connection cable (up to two provided per trailer).

Electric Cable: 25ft cable to plug into a common 120V outlet.



STEADYPOWER SP-LREL12 CABLE REEL COVER

Door: Open upwards with gas-assisted vertical lift.

Security: Doors have hasps for customer-supplied padlocks.

Enclosure: Steel with stainless steel fasteners and vents.

Paint: Heavy-duty primer and powder-coating.



STEADYPOWER LB2800A-25-W40-50-OYBG CABLE SET

Number of Sets Included: Two.

Number of Cables per Set: Twenty-five (7 per phase, 4 ground).

Cable Length: 50ft. (Two sets offer a total of 100ft length).

Cable Specs: 4/0 Type W single conductor flexible cable with color-coded male and female cams

Cam Colors: Orange, Yellow, and Brown for each phase, Green for ground.



We offer everything you need for a Trailer-Mounted Load Bank!

3300 Jefferson Ave. SE, Grand Rapids, MI 49548

Phone: 616-452-8708, 1-800-852-7699

Email: customerservice@steadypower.com

Coffman 
Electrical Equipment Co.
STEADYPOWER.COM
Complete Critical Power Solutions