Universal R2000H Trailer-Mounted Load Bank Package

Our Universal R2000H Trailer-Mounted Resistive Load Bank Package offers a ULB 2000kW load bank, our heavy-duty trailer, our two cable reels with reel covers, and two cable sets.





ULB R2000H LOAD BANK

Load Capacity: 2000kW at 480VAC 3PH 60Hz, 1000kW at 240VAC 3PH 60Hz, & 750kW at 208VAC 3PH 60Hz.*
Full Load Amps at 1000kW: 2406 Amps at 240 VAC.
Full Load Amps at 2000kW: 2406 Amps at 480 VAC.
Duty Cycle: Rated for continuous operation.
Load Step Resolution: 25kW at 240/480V.
Controls: Local digital color touchscreen controller.
Instrumentation: Digital metering (V, A, kW) and data logging.
Control Power: Control power via internal dual voltage transformer or from external 120V 1Ph source.
Cooling Power: Blower power from connected load or external 480/240 3Ph source.
Cooling System: Integral forced-air cooling system with horizontal airflow. Removable sliding covers with lock pins on air intakes and exhausts.
Load Elements: ULB high-capacity chromium alloy load elements. Elements are fully supported with stainless steel rods and high temperature refractory ceramics for quick heat discharge.
Safety Features: Over-temperature, over/under voltage, and cooling-air loss protection. Also includes a hard-wired emergency stop switch.
Load Connections: Quick disconnect cam-type male connectors (10 per Phase, 3 Ground).
Daisy Chained: Multiple load banks can be paralleled for higher load capacity, and operated from a single controller.
Enclosure: Heavy gauge steel outdoor enclosure with powder coat finish. Designed to NEMA 3R standards for outdoor operation. Hinged access doors. Forklift pockets for easy mobility.

***** Capacity rated up to 2,000 feet elevation from sea level. Please inquire for higher elevations.

Coffman Electrical Equipment Company, 3300 Jefferson Ave. SE, Grand Rapids, MI 49548
Phone: 616-452-8708, 1-800-852-7699 - Email: customerservice@steadypower.com

STEADYPOWER SP2-9900-210×99 TRAILER



Trailer: Galvanized steel.
GVWR: 9900 lbs.
Bed Size: 210" L x 99" W.
Axles: Tandem. Each axle rated 6,000 lbs.
Tires: Four Wheel-Mounted Goodyears.
DOT Approved: Lighting and 7-pin Electrical Connections.
Brakes: Electric.
Hitch: Choice of Ball or Pintle Hitch.
Jacks: One 7000-lbs Front Tongue Jack and Two Rear Swing-up Stabilizer Jacks.
Safety: Chains and Hooks.
D-Rings: Four Heavy-Duty.
Spare Tire: Mounted Goodyear.



STEADYPOWER SP-HRXECV-115VAC-1250 CABLE REEL

Linear Feet Capacity: Each reel holds up to 1250 ft of 4/0 cable.
50ft Cables Capacity: Each reel holds up to twenty-five 50ft 4/0 cables with cams.
Unwind/Rewind: 115VAC Electric motor with variable speed control and rocker switch.
Brake: Bearing mounted strap brake.
Hand Control: Enhanced push button switch.
Bonus Foot Control: Foot switch with 15ft connection cable (up to two provided per trailer).
Electric Cable: 25ft cable to plug into a common 120V outlet.

STEADYPOWER SP-LREL12 CABLE REEL COVER

Door: Open upwards with gas-assisted vertical lift.
Security: Doors have hasps for customer-supplied padlocks.
Enclosure: Steel with stainless steel fasteners and vents.
Paint: Heavy-duty primer and powder-coating.



STEADYPOWER LB2800A-25-W40-50-OYBG CABLE SET



Number of Sets Included: Two.
Number of Cables per Set: Twenty-five (7 per phase, 4 ground).
Cable Length: 50ft. (Two sets offer a total of 100ft length).
Cable Specs: 4/0 Type W single conductor flexible cable with color-coded male and female cams
Cam Colors: Orange, Yellow, and Brown for each phase, Green for ground.

We offer everything you need for a Trailer-Mounted Load Bank!

3300 Jefferson Ave. SE, Grand Rapids, MI 49548
Phone: 616-452-8708, 1-800-852-7699
Email: customerservice@steadypower.com

Coffman Electrical Equipment Co.
STEADYPOWER.COM
Complete Critical Power Solutions